

Niroplast

Product Description

Excellent washable plastic paint for interior walls. Highly durable over time, does not turn yellow, breathes. The paint possesses good coverage and concealment.

Typical Uses

Intended for painting interior walls in apartment buildings, institutions, public buildings etc. Suitable for painting new walls after appropriate surface preparation and for application on Wonderspeed filler or directly on existing paint.

Surface Preparation

In order to obtain good results, the surface must be prepared thoroughly and carefully. Clean the surface well to remove any foreign body such as old whitewash, dust, old peeling paint, grease etc. Make sure the old paint left on the wall is firmly attached to the infrastructure. Remove loose paint with a mortar and sandpaper.

Application

Brush, roller or sprayer (airless) Dilute according to the instructions. First mixing must be done without the addition of water.

Clean Up

Tools can be cleaned with soap and water immediately after use.

Finish

Shade: White. Gloss level: matte.

Physical Properties

Contains: A water and mineral substance-based acrylic mixture.

Dilution: In water, up to 20% for the first coat, up to 15% for additional coats.

Coverage*: 6-7m2/l in two coats

The coverage capability is calculated according to the work of a skilled laborer on an infrastructure with an ordinary degree of absorption and may vary according to the working method, surface and weather conditions.

Limitations

Do not apply the material when the temperature is below 7°C.

Dry time

To recoat: 2-3 hours

(under ordinary weather conditions).

Totouch: 4 hours. Full cure: 24 hours.

Shelf-life & Storage

12 months in a closed bucket, in cool and dry place.

Packaging

3 liters, 5 liters and 18 liters.

Health and Safety Precautions: The material does not contain lead. During application it is advisable to wear goggles and ensure that the site is adequately ventilated. If the paint comes in contact with the eyes, rinse well under running water and seek medical assistance. Keep the package tightly closed. Do not hang on the handle. Keep away from children. Do not mix materials not recommended by Niriat. General Notes: The aforementioned recommendations are not to be perceived as a substitute for consultation in writing specific work specifications. All the data and recommendations presented here are based on tests, knowledge and experience that have accumulated in the laboratory and on-site and they are highly reliable. This is not to be interpreted as a general warranty, either explicit or implicit. The warranty is for product quality only. The user must examine the suitability thereof for his purposes. We reserve the right to update or change the data without prior notice.