

SUPERCRYL MATT FINISH

High Quality, Highly Durable, Water Based Acrylic Paint for Exterior and Interior Walls

SPECIAL FEATURES

Provides an elegant look and high, long-term durability. Does not peel off or fade. High spreading rate, fast drying, breathing paint, lead and chromates free.

SUGGESTED USES

Painting interior and exterior plastered walls, concrete and bricks walls.

TECHNICAL DATA

Product code: 732-2xx (White +4 bases)
 Color: 1200 colors from Tambour Spectrum fan deck.
 Gloss: Matt
 Calculated spreading rate*: 8-9 sq.m/liter (for white in two coats) 6-7 sq.m/ liter (for shades in two coats).
 Recommended Thinner: **During application:** water. **For cleaning:** water and soap.
 Drying Times: **Touch dry**:** 1 hour. **Hard coat:** 3 hours **Dry to recoat:** 3 hours **Completely dry for cleaning and washing:** 7 days after application
 Shelf life: 24 months
 Quantity per Pallet:

Package size	Quantity per Pallet
18 liters	36
15 liters	36
10 liters	36
5 liters	80
3 liters	210
1 liter	576

SURFACE PREPARATION AND PAINT SYSTEM

Interior Whitewashed Lime surfaces

Remove any loose, flakey, peeling lime or excessively thick layers. Sand with sandpaper to a smooth surface. Clean off dust thoroughly. Apply one coat of **Bonderol Super**. Allow to dry for 4 hours and apply two coats of **Supercryl Matt Finish**.

Painted Interior Walls

Remove any old, loose and peeling paint. Apply a coat of **Bonderol Super** on peeling paint surfaces. Smooth the surface by applying **Magic Bond** or **Glue Putty 2000** (for interior applications only), apply a coat of **Bonderol Super** over it and allow to dry. Apply 2-3 coats of **Supercryl Matt Finish**. When the old paint coat is whole and cannot be removed, apply 2-3 coats of **Supercryl Matt Finish** directly on it.

New, Unpainted, Plastered Interior Walls

Smooth the surface lightly using sandpaper. Remove dust and fill holes with **Calcimo X**. To obtain a smooth surface, apply a coat of **Tambourfill** and allow drying for 4 hours. Apply 2-3 coats of **Supercryl Matt Finish**.

Concrete and Cement Plaster Surfaces

Paint can be applied only after the plaster is completely cured (one month or more after application). Remove dust and apply a first coat of white **Bonding Primer White** diluted by about 30% with Tambour Mineral white spirit. Allow to dry for 24 hours at least. Apply 2-3 coats of **Supercryl Matt Finish**.

APPLICATION REMARKS

Stir the paint well before application and while painting.

Apply using a brush/ Roller/ Airless:

Dilute the paint with water for the first coat by 20% - 30% and stir well. Dilute the paint with water for the additional coats by 10%-20%. Apply 2-3 coats, according to the surface type.

CLEANING AND STORAGE

Clean work tools with soap and water, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us.

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

Notes:

- Washable & scrubbing resistant & heavy-duty
- Water based emulsion paint,
- For indoor & outdoor use
- User & Environment Friendly

* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site.

Assume approximately 75% of the calculated spreading rate.

** at 25°C and 65% relative humidity.

SUPERCRYL 2000 FREE

"Green", User and Environment Friendly, Odorless Acrylic Paint

SPECIAL FEATURES:

Excellent and unique acrylic paint combining user and environment protection properties with high product quality.

With very low VOC (organic hydrocarbon emission) properties, odor free Green SUPERCRYL is the ideal choice for users who are sensitive to odors during and after the application. Green SUPERCRYL may be applied in populated spaces without removing the occupants, e.g., hospitals, children rooms, etc.

SUPERCRYL 2000 provides high coverage rate, in bright white, without any brush marks, that lends a very elegant look to the wall.

Awarded the green label by the Standards Institute.

SUGGESTED USES:

For interior application.

TECHNICAL DATA:

Product Code: 728-101 white, 728-102 pastel base, 728-103 median base, 728-104 deep base, 728-105 transparent base.

Color: White, 1200 shades of the spectrum chart and any shade of the other charts in the market.

Gloss: Matt-satin.

Calculated spreading rate*: 6-7 sq.m/liter (in two coat)

Recommended Thinner: During Application: water **Cleaning:** water and soap.

Drying Times: Touch dry**: 1 hour; **Hard Coat:** 3 hours. **Dry to recoat:** 2-3 hours

Drying for cleaning and washing the wall: 7 days

Shelf life: 24 months

Quantity per Pallet:	Package size	Quantity per Pallet
	18 Liters	36
	15 Liters	27
	10 Liters	44
	5 Liters	80
	3 Liters	210
	1 Liter	576

SURFACE PREPARATION AND PAINT SYSTEM:

Interior whitewashed surfaces:

Remove any free, loose, peeling white wash or very thick coats. Use sandpaper to obtain a smooth surface. Clean the dust thoroughly. Apply one coat of BONDROL SUPER and allow to dry for 4 hours. Apply two coats of SUPERCRYL 2000 Green in an elegant look, diluted with 5% - 10% water.

Interior walls painted with plastic paint:

Remove any old, loose, peeling paint. Apply one coat of BONDROL SUPER on peeled paint areas. Smooth the surface using MAGIC BOND SUPER or PUTTY ADHESIVE 2000 (for interior application only) and apply one coat of BONDROL SUPER. Apply 2-3 coats of SUPERCRYL 2000 Green in an elegant look

New unpainted interior walls (finishing plaster):

Use sandpaper to smooth the surface lightly. Remove the dust and fill holes with CALCIMO X or with CALCIMO FINE. Apply 1-2 coats of TAMOURFILL diluted with 5% - 10% water and allow to dry for 4 hours. Apply the first coat of SUPERCRYL 2000 Green in an elegant look, diluted with 5% - 10% water and apply a second and third coat of SUPERCRYL 2000 Green in an elegant look, diluted with 5% - 10% water, as needed.

PAINT APPLICATION:

Mix the paint thoroughly before application and during application,

Roller Application:

Dilute with 5% - 10% water and mix thoroughly. Dip the roller in the paint and remove excess paint (in the 5 liters oval container, you can dip the roller directly in the container). Apply 2-3 coats according to the surface type. Apply until the surface is completely covered and then roll lightly in crisscross movements to obtain an elegant, uniform look.

Brush/ Pad Application:

Pour the paint into another container. Dilute with 5% - 10% water and mix thoroughly. Apply 2-3 coats according to the surface type.

Please note: in shades based on A and D bases, apply one coat of primer for interior walls, red or yellow (according to the applied shade), specifically suited for use as a primer for top acrylic paints. Application of one coat of primer for interior walls ensures maximum coverage and exact shade of the top coat. Then apply SUPERCRYL 2000 Green in an elegant look according to the instructions.

TOOLS CLEANING AND STORAGE:

Clean the tools with water and soap immediately upon completing the application. Pour a thin layer of water on the remaining paint and close the container tightly, to prevent air penetration. Store in a roofed, ventilated place.

CAUTION:

Inedible. The product is not defined as a hazardous material and does not contain materials that require special marking or warning. Keep away from children. Provide adequate ventilation of the work space. Read the applicable information on the product in the Safety Data Sheet (MSDS).

GENERAL COMMENTS:

Do not apply the paint when rain is expected and/or when walls temperature falls below 10 degrees Celsius and relative humidity exceeds 85%. Do not mix this product with products that are not recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* Practical spreading rate depends on several factors: The surface, the application mode, color shades, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

** At 25°C and 65% relative humidity.

IS 1945 + scrubbing table, green label, 7 years warranty.

Produced by Tambour, authorized by the Israeli Institute of Standards, complying with ISO 9001.

SUPERCRYL MD.

High Quality, Water Based Acrylic Paint Especially Suited for Exterior Walls: Provides Complete Protection Against extreme Climate Conditions and Concrete Salts Damage

SPECIAL FEATURES

Especially high durability in extreme climate conditions. Long-term retention of color and wall appearance. Superior adhesion to the substrate. Resists concrete salts damage. Breathing, environment friendly, lead and chromates free.

SUGGESTED USES

Painting exterior plastered walls, concrete and bricks walls.

TECHNICAL DATA

Product code:	734-400 white, 734-402 P based, 734-403 T based, 734-404 D based, 734-405 A based.	
Color:	White and 1200 colors from Tambour Spectrum fan deck.	
Gloss:	Matt	
Calculated spreading rate*:	6 sq.m/liter (in two coats)	
Recommended Thinner:	During application: water. For cleaning: water and soap.	
Drying Times:	Touch dry**: 1 hour. Hard coat: 7 days. Dry to recoat: 2-3 hours 2 days before	
Shelf life:	24 months	
Quantity per Pallet:	Package size 18 liters	Quantity per Pallet 27

SURFACE PREPARATION AND PAINT SYSTEM

Concrete and Cement Exterior Plaster Surfaces

Paint can be applied only after the plaster is completely cured (one month or more after application). Remove dust and apply a first coat of **Tambourflex Primer White** diluted by about 30% mineral white spirit (applied by brush, roller or spray). Allow to dry for 24 hours at least and apply 2 coats of **Supercryl M.D.**

Painted Walls

Remove any old, loose and peeling paint. Use **Exterior Acrylic Putty** to smooth and fill holes. Allow to dry and sand with sandpaper to obtain a smooth surface. Fill any structural cracks with **Tambourflex Filler**. Apply 2 coats of **Supercryl M.D.**, diluted as required.

APPLICATION REMARKS

Stir the paint well before application and while painting.

Apply using a brush/ Roller/ Airless: Dilute the paint with water for the first coat by 20% - 30%. Dilute the paint with water for the additional coats by 10%-20%.

CLEANING AND STORAGE

Clean work tools with soap and water, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site.

Assume approximately 75% of the calculated spreading rate.

** at 25°C and 65% relative humidity.

SUPERCRYL M.D. SILICONE

High Quality, Water Based Acrylic Paint Especially Suited for Exterior Walls: Provides Complete Protection Against extreme Climate Conditions and Concrete Salts Damage

SPECIAL FEATURES

Special Features: Especially high durability in extreme climate conditions. High resistance to humid condition with excellent water vapor permeability. Long-term retention of color and wall appearance. Superior adhesion to the substrate. Resists concrete salts damage. Breathing, environment friendly, lead and chromates free.

SUGGESTED USES

Painting exterior plastered walls, concrete and bricks walls.

TECHNICAL DATA

Product code:	737-400 white, 737-402 P based	
Color:	White and 400 colors from Tambour Spectrum fan deck.	
Gloss:	Matt	
Calculated spreading rate*:	6 sq.m/liter (in two coats)	
Recommended Thinner:	During application: water. For cleaning: water and soap.	
Drying Times:	Touch dry**: 1 hour. Hard coat: 7 Days Dry to recoat: 2-3 hours	
Shelf life:	24 months	
Quantity per Pallet:	Package size	Quantity per Pallet
	18 liters	27

SURFACE PREPARATION AND PAINT SYSTEM

Concrete and Cement Exterior Plaster Surfaces

Paint can be applied only after the plaster is completely cured (one month or more after application).

Remove dust and apply a first coat of **Tambourflex Bonding Primer** diluted by about 30% mineral white spirit (applied by brush, roller or spray). Allow to dry for 24 hours at least and apply 2 coats of **SUPERCRYL M.D. SILICONE**

Painted Walls

Remove any old, loose and peeling paint. Use **Exterior Acrylic Putty** to smooth and fill holes. Allow to dry and sand with sandpaper to obtain a smooth surface. Fill any structural cracks with **Tambourflex Filler**. Apply 2 coats of **SUPERCRYL M.D. SILICONE**, diluted as required.

APPLICATION REMARKS

Stir the paint well before application and while painting.

Apply using a brush/ Roller/ Airless: Dilute the paint with water for the first coat by 20% - 30%. Dilute the paint with water for the additional coats by 10%-20%.

CLEANING AND STORAGE

Clean work tools with soap and water, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site.

Assume approximately 75% of the calculated spreading rate.

** at 25°C and 65% relative humidity.

Supercryl More

A water-based acrylic paint with excellent coverage capabilities. Good for indoor and outdoor applications

Features:

Provides extremely high coverage and an attractive and highly durable appearance – does not peel or fade. Quick drying and breathing paint. Meets Israeli Standard 1945 for internal and external paints, has low VOC, and possesses Green Seal 1738.

Uses:

For internal and external painting of plaster, concrete and brick walls.

Technical Specifications:

Product Code:	White: 732-501	Pastel Base 732-502
Colour:	White and 400 pastel shades from Tambour Spectrum fan deck.	
Surface:	Matt	
Calculated Coating Ability*:	9-10 sq meters/liter (two coats)	
Recommended Thinner:	Water	Cleaning: Soap and Water
Setting Time:	Dry to Touch**: 1 hour	Hard Setting: 3 hours (7 days before rain). Dry to recoat: 2-3 hours
Shelf Life:	24 Months	
Quantity per Pallet:		
	Package Size	Quantity per Pallet:
	18 liters	27
	10 Liters	60

Surface and Paint System Preparation

Whitewashed Internal Areas:

Remove any free, loose or too-thick whitewash. Sand until smooth. Clean well of dust. Apply one coat of **Bonderol Super** and wait 4 hours until dry. Apply two coats.

Internal Walls Painted with Plastic Paints:

Remove old, loose or peeling paint. Apply **Bonderol Super** where paint is peeling. Smooth surface with **Magic Bond** or **Glue Putty 2000** (indoor use only), coat with **Bonderol Super** and wait until dry. Apply two coats of **Supercryl More**.

If the old paint is in good condition and cannot be removed, apply directly 2 coats of **Supercryl More**.

Unpainted new Internal Walls:

Gently sand the surface. Remove dust and fill holes with **Calismo X**. For a smooth surface apply coat of **Magic Bond** or **Tambourfill** and wait until fully dry. If **Magic Bond** is applied, a layer of **Bonderol Super** is necessary. Apply 2 coats of **Supercryl More**.

Concrete and Cement Plaster Surfaces:

Paint only after finishing (at least a month after application). Clean dust, and apply first coat of **Tambourflex Bonding Primer**, diluted with 30% mineral turpentine. After at least 24 hours, apply 2 coats of **Supercryl More**.

Application

Stir well before use and occasionally throughout application. Brush/roller/spray painting – dilute first layer of paint with 20%-30% water and mix well. Dilute paint of additional layers with 10%-20% water. Apply 2 coats according to surface.

Tool Cleaning and Storage

Clean work tools with water and soap immediately after finishing work. Pour thin layer of water on remaining paint and seal packaging against air. Store in covered and ventilated place.

Warnings and Safety Instructions:

The paint is not to be eaten; the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Specific information regarding the product is available in the safety manual (MSDS).

General Notes:

Do not apply when rain is expected and/or the wall temperature is under 10°C and the relative humidity is over 85%. Do not mix this product with products not recommended by us. Achieving desired results is contingent upon following all instructions concerning the proper application of the product. Prior to applying the product, the user must make sure that application of the product is in the intended manner, and that the surface to be painted and its infrastructure have been properly prepared and appropriate to the product's application.

The information presented is based on knowledge and experience accumulated over the course of years. We reserve the right to update and/or change it at our discretion.

* The actual coverage is contingent on several factors: the surface, the manner of painting, the color, the painter's expertise and on-site weather conditions. The assumption is that it consists of 75% of the calculated coverage capability.

** At 25°C and 65% relative humidity.

SUPERCRYL ONE COAT

High Quality Water Based Acrylic Paint Suitable for Supercryl One Coat Application

Special Features

Enables fast and easy application in one coat, washable, fast drying, breathing paint, lead and chromates free

Suggested Uses

Specially designed for frequent wall painting in children rooms, living rooms, bedrooms, corridors and balconies.

Technical Data

Code No.	731-501 White,
Colour	Snow white + 9 colours (see colour chart).
Gloss	Matt.
Calculated spreading rate*:	8 sqm/liter (in one coat)
Recommended Thinner	Water
Cleaning Thinner	Water and soap.
Touch dry **	1 hour
Hard dry **	3 hours
Dry to recoat **	3-4 hours
Shelf life **	24 months

Application Method

By Roller

Put the grid inside the can with its lower part immersed in the paint and its upper part leaning on the can side.

Immerse the roller directly into the oval can, without thinning. Remove excess paint with the grid and spread evenly in one thick coat. For excellent finish it is recommended to paint the wall until full coverage and then roll slightly in a crosswise motion.

By Brush or Pad

Thin with up to 15% water (3 glasses for one can).

Surface Preparation and Specification

Internal white washed surfaces lime

Remove loose or peeling material or too thick layers. Use sandpaper to reach a smooth surface. Clean off dust thoroughly. Apply Supercryl One Coat of **Bonderol Super** and allow 4 hours to dry. Apply Supercryl One Coat in one coat.

Internal walls painted with plastic paint

Remove loose or peeling material. Peeling areas should be painted with **Bonderol Super**. Smooth the surface until even with **Glue Putty 2000** or **Superbond**. Apply Supercryl One Coat of **Bonderol Super** and

allow 4 hours to dry. Apply Supercryl One Coat of **One Coat**. If the old paint is in good condition and cannot be removed. **Supercryl One Coat** may be applied directly.

External plaster and concrete surfaces

New well aged (at least 1 month after application plaster and concrete surfaces must be thoroughly cleaned from dust. Apply Supercryl One Coat of **Bonding Primer** thinned with 30% mineral spirit. After min. 24 hours apply one coat of Supercryl One Coat.

- In case the painting instructions are not fully applied, a second layer may be needed, especially on dark coloured walls.

CLEANING AND STORAGE

Clean work tools with water and soap, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us.

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site.

Assume approximately 75% of the calculated spreading rate.

** at 25°C and 65% relative humidity.

SUPERCRYL CLEAN

Premium acrylic paint protects and allows fast and easy cleaning.

SPECIAL FEATURES

Provides an elegant look and high, long-term durability. Specially designed for frequent cleaning in children rooms and corridors. Breathing paint, lead and chromates free.

SUGGESTED USES

Painting interior plastered walls.

TECHNICAL DATA

Product code:	724-10x (White +4 bases)	
Color:	1200 colors from Tambour Spectrum fan deck.	
Gloss:	Matt	
Calculated spreading rate*	5-6 sq.m/liter (in two coats)	
Recommended Thinner:	During application: water. For cleaning: water and soap.	
Drying Times:	Touch dry**: 2-3 hour. Hard coat: 24 hours Dry to recoat: 4 hours Completely dry for cleaning and washing: 7 days after application	
Shelf life:	24 months	
Quantity per Pallet:		
	Package size	Quantity per Pallet
	5 liters	120
	18 liters	36

SURFACE PREPARATION AND PAINT SYSTEM

Interior Whitewashed Lime surfaces

Remove any loose, flakey, peeling lime or excessively thick layers. Sand with sandpaper to a smooth surface. Clean off dust thoroughly. Apply one coat of **Bonderol Super**. Allow to dry for 4 hours and apply two coats of **Supercryl Clean**.

Painted Interior Walls

Remove any old, loose and peeling paint. Apply a coat of **Bonderol Super** on peeling paint surfaces. Smooth the surface by applying **Magic Bond** or **Glue Putty 2000** (for interior applications only), apply a coat of **Bonderol Super** over it and allow to dry. Apply 2-3 coats of **Supercryl Clean**. When the old paint coat is whole and cannot be removed, apply 2-3 coats of **Supercryl Clean** directly on it.

New, Unpainted, Plastered Interior Walls

Smooth the surface lightly using sandpaper. Remove dust and fill holes with **Calcimo X**. To obtain a smooth surface, apply a coat of **Tambourfill** and allow drying for 4 hours. Apply 2-3 coats of **Supercryl Clean**.

Concrete and Cement Plaster Surfaces

Paint can be applied only after the plaster is completely cured (one month or more after application). Remove dust and apply a first coat of white **Bonding Primer White** diluted by about 30% with Tambour Mineral white spirit. Allow to dry for 24 hours at least. Apply 2-3 coats of **Supercryl Clean**.

APPLICATION REMARKS

Stir the paint well before application and while painting.

Apply using a brush/ Roller/ Airless:

Dilute the paint with water for the first coat by 20% - 30% and stir well. Dilute the paint with water for the additional coats by 10%-20%. Apply 2-3 coats, according to the surface type.

CLEANING AND STORAGE

Clean work tools with soap and water, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us.

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

Notes:

- Washable & scrubbing resistant & heavy-duty
- Water based emulsion paint,
- For indoor & outdoor use
- User & Environment Friendly

* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site.

Assume approximately 75% of the calculated spreading rate.

** at 25°C and 65% relative humidity.

SUPERCRYL EGGSHELL FINISH

Premium, Water Based Acrylic Paint for Exterior and Interior Walls for elegant finish

SPECIAL FEATURES

Excellent spreading rate, elegant finish, enables water vapors passage (breathing).
Lead and chromates free.

SUGGESTED USES

Painting interior and exterior plastered walls concrete and bricks walls.

TECHNICAL DATA

Product code: 723-101 white, 723-102 P based, 723-103 T based, 723-104 D based, 723-105 A based.
Color: White and 4 Bases.
Gloss: Eggshell
Calculated spreading rate*: 7 sq.m/liter (in two coats)
Recommended Thinner: **During application:** water, **For cleaning:** water and soap.
Drying Times: **Touch dry**:** 1 hour. **Hard coat:** 3 hours **Dry to recoat:** 2-3 hours **Completely dry for cleaning and washing:** 7 days after application
Shelf life: 24 months
Quantity per Pallet:

Package size	Quantity per Pallet
1 liter	576
2.5 liters	210
5 liters	80
10 liters	44
18 liters	27

SURFACE PREPARATION AND PAINT SYSTEM

Interior Whitewashed Lime surfaces

Remove any loose, flakey, peeling lime or excessively thick layers. Sand with sandpaper to a smooth surface. Clean off dust thoroughly. Apply one coat of **Bonderol Super** primer. Allow to dry for 4 hours and apply two coats of **Supercryl 2000** diluted by 10%-20% water.

Painted Interior Walls

Remove any old, loose and peeling paint. Apply a coat of **Bonderol Super** primer on peeling paint surfaces. Smooth the surface by applying **Magic Compound** or **Glue Putty 2000** (for interior applications only), apply a coat of **Bonderol Super** primer over it and allow to dry. Apply 2-3 coats of **Supercryl Eggshell Finish**.

New, Unpainted, Plastered Interior Walls

Smooth the surface lightly using sandpaper. Remove dust and fill holes with **Calcimo X**. To obtain a smooth surface, apply 1-2 coats of **Tambourfill** diluted by 5%-10% water and allow to dry for 4 hours. Apply first coat of **Supercryl Eggshell Finish** diluted by 20%-30% water. Apply second and third coat as required, diluted by 10%-15%.

Concrete and Cement Plaster Surfaces

Paint can be applied only after the plaster is completely cured (one month or more after application). Remove dust and apply a first coat of **Supercryl Eggshell Finish** diluted by about 30% water. Apply the second and third coats of **Supercryl Eggshell Finish** diluted by 10%-20% water. Allow to dry for 3 hours between coats.

APPLICATION REMARKS

Stir the paint well before application and while painting.

Roller Application: Dilute by 10% water and stir well. Dip the roller in paint and then remove excess paint (in the oval, 5 liters container, you can dip the roller directly in the container). Apply 2-3 coats according to the surface type. To obtain a nice and uniform finish, cover the entire wall and then finish by light crisscross rolling.

Brush/ Pad application: Pour the paint into another container. Dilute by 15%- 20% water and stir well. Apply 2-3 coats according to the surface type.

CLEANING AND STORAGE

Clean work tools with soap and water, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us.

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

** at 25°C and 65% relative humidity.