

VenusGlass Balls on a Flexible Base

Product Description

A covering set covered with tiny glass balls in various sizes, giving the surface a sparkling glassy look in a wide variety of colors and effects. Interior and exterior covering with outstanding exterior durability and flexibility and a unique appearance. A multicolored reflection is obtained in sunlight and artificial light. The covering is available in a large number of background shades, according to the Nirlat color fan, and the sparkly reflective effect is available in various shades of glass.

Typical Uses

On any existing infrastructure, wood, plaster, gypsum and more. We recommend consulting with a Nirlat consultant with regard to each infrastructure.

Application

The infrastructure must be flat and smooth, flat and strong cement spackle on exterior walls and smooth interior walls. Apply white Primer X with a weight of 200-250 gr/m² and let dry for 6 hours at least. Apply smooth Canitex Super Flexible in the desired shade, using a roller or sprayer, with a weight of 1 kg/m² at least, and in a single coat. Dry spraying of the glass balls is performed immediately after application of Super Flexible. Spray at low pressure to prevent the balls from falling off the surface, insofar as possible. Spray the balls so that they cover the Super Flexible completely and uniformly. Spray the wall without stopping. Protective goggles and a mask must be worn. The suggested quantity of glass is 1-1.5 kg/m².

Our expert's recommendation

Practice the spraying technique on a small area before starting the project. Cover the floor with polyethylene sheeting and cardboard in order to prevent slipping. Glass balls that fall can be collected for reuse.

Lighting: Lighting plays a decisive role in the final appearance. We recommend spotlight illumination at a distance of three meters, in order to obtain a splendid appearance of multicolored glass balls in the light.

Finish

Shades: 1,500 shades according to the Nirlat color fan Glass ball finish: Clear or colors, according to the catalogue.

Packaging

Base 5 liters. Glass balls 6 kg.

Health and Safety Precautions: The material does not contain lead. During application it is advisable to wear goggles and ensure that the site is adequately ventilated. If the paint comes in contact with the eyes, rinse well under running water and seek medical assistance. Keep the package tightly closed. Do not hang on the handle. Keep away from children. Do not mix materials not recommended by Nirlat. General Notes: The aforementioned recommendations are not to be perceived as a substitute for consultation in writing specific work specifications. All the data and recommendations presented here are based on tests, knowledge and experience that have accumulated in the laboratory and on-site and they are highly reliable. This is not to be interpreted as a general warranty, either explicit or implicit. The warranty is for product quality only. The user must examine the suitability thereof for his purposes. We reserve the right to update or change the data without prior notice.